



The BenweldSecure Custom Strategic Rooms (CSR) are tested and certified up to LPS 1175 Issue 8: Security Ratings to protect high-security high-profile individuals and confidential information against deliberate forced entry attempts using a wide range of conventional hand tools. The modular design allows for easy transportation, custom sizes, and quick assembly in hard-to-access areas of a building.

Government-approved options available for additional protection against surreptitious, acoustic and radio frequency attacks.

#### FEATURES:

- Tested and certified to LPS 1175 Issue 8: Security Ratings A1 (SR1), B3 (SR2), B20, C3, C5 (SR3), D10 (SR4), E10 (SR5) & G5
- Supplied with approved accessories
- 50% faster construction time than a traditional build
- Designed to be assembled from the inside to help optimise space management
- Flexible sizing to suit any requirement
- Easily configured to match your existing facility with a choice of colours and finishes

#### DETAILS

|                              |                                                                                                                                                                                                         |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT REFERENCE:</b>    | BenweldSecure Custom Strategic Rooms (CSR)                                                                                                                                                              |
| <b>SECURITY RATING:</b>      | LPS 1175: Issue 8 Security Rating up to G5 and government-approved options*                                                                                                                             |
| <b>FIRE RATING:</b>          | Tested to BS 476-22 and achieves up to 120 minutes integrity/120 minutes insulation - fire requirement may have an impact on panel thickness, and fire-rated applications must use a rockwool core type |
| <b>THERMAL RATING:</b>       | Up to 0.17 W/m <sup>2</sup> K (PIR Core)                                                                                                                                                                |
| <b>ACOUSTIC RATING</b>       | Up to Rw 65dB (Rw +/- 3dB)                                                                                                                                                                              |
| <b>FINISH:</b>               | Available in a variety of colours and finishes to match your existing facility                                                                                                                          |
| <b>CONSTRUCTION DETAILS:</b> | Walling panels available up to 5 m long and can be used for ceiling panels up to 3 m in span                                                                                                            |
| <b>INSTALLATION:</b>         | Please contact BenweldSecure for installation options and costs                                                                                                                                         |
| <b>APPROVED ACCESSORIES:</b> | Penetrations**<br>Doorsets**<br>Louvres**<br>Windows & Glazing**                                                                                                                                        |

For specific information on our fire, acoustic and thermal specifications, please get in touch with us - sales@benweld.co.uk

\* For specific information on our government-approved options, please get in touch with us - sales@benweld.co.uk.

\*\* For specific information on our approved accessories, please get in touch with us - sales@benweld.co.uk.